

Cell SFP

Small Form-Factor Pluggable Transceiver 155Mbps SFP

Product Overview

Features

- Support SDH STM-1/SONET OC-3/100Mbps Fast Ethernet
- Industry Standard Small Form Pluggable (SFP) Package
- Wavelength : 1310nm/ 1550nm
- Bit Rate : up to 155Mbps
- Power Supply : 3.3 Voltage
- Differential LVPECL Inputs and Outputs
- Connector type : Duplex LC for standard 155M SFP
- Class 1 laser product complies with EN60825-1
- With and without Diagnostic Monitoring (DM)
- Hot Pluggable



155M SFP

155Mbps SFP

Model No.	Data Rate	Wavelength/ Light Source	Media Type	Reach	TX Power (dBm)	RX Sens. (dBm)	Temp. (°C)	Notes
SFP-155-02	155 Mb/s	1310nm (LED)	MMF	2 km	-14 ~ -20	<-31	0 ~ 70	
SFP-155-30	155 Mb/s	1310nm (FP)	SMF	30 km	-8 ~ -15	<-34	0 ~ 70	
SFP-155-60	155 Mb/s	1310nm (FP)	SMF	60 km	0 ~ -5	<-35	0 ~ 70	
SFP-155-20	155 Mb/s	1550nm (DFB)	SMF	20 km	0 ~ -5	<-34	0 ~ 70	
SFP-155-100	155 Mb/s	1550nm (DFB)	SMF	100 km	0 ~ -5	<-35	0 ~ 70	
SFP-155-120	155 Mb/s	1550nm (DFB)	SMF	120 km	+5 ~ 0	<-35	0 ~ 70	
SFP-155-2-DM	155 Mb/s	1310nm (LED)	MMF	2 km	-14 ~ -20	<-31	0 ~ 70	With DM
SFP-155-30-DM	155 Mb/s	1310nm (FP)	SMF	30 km	-8 ~ -15	<-34	0 ~ 70	With DM
SFP-155-60-DM	155 Mb/s	1310nm (FP)	SMF	60 km	0 ~ -5	<-35	0 ~ 70	With DM
SFP-155-20-DM	155 Mb/s	1550nm (DFB)	SMF	20 km	0 ~ -5	<-34	0 ~ 70	With DM
SFP-155-100-DM	155 Mb/s	1550nm (DFB)	SMF	100 km	0 ~ -5	<-35	0 ~ 70	With DM
SFP-155-120-DM	155 Mb/s	1550nm (DFB)	SMF	120 km	+5 ~ 0	<-35	0 ~ 70	With DM

About Cell Technology

Cell Technology headquartered at Hong Kong SAR, a network & security technology provider specializes in design, develop and deliver innovative and intelligent IP packet processing platform into software and hardware appliances. Cell product solutions including Cell IPS, UTM, CMC, Janus, TMS, NetsVision and NetsAccess address the business needs that optimize the IP network performance, secure the network security and resiliency, and manage the quality of IP services. For more information, please visit www.cell-technology.net.